


FORM PTO-1390		U S Department of Commerce Patent and Trademark Office	Attorney's Docket No. 2530-109
<b>TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371</b>			U.S. Application No. (if known, see 37 CFR 1.5) <b>09/720102</b>
INTERNATIONAL APPLICATION NO. PCT/FI99/00568	INTERNATIONAL FILING DATE June 28, 1999	PRIORITY DATE CLAIMED June 29, 1998	
<b>TITLE OF INVENTION</b> A PROCESS FOR THE PREPARATION OF COMPOUND FERTILIZER GRANULES			
<b>APPLICANT(S) FOR DO/EO/US</b> Arthur VAN BREMPT and Juhani POUKARI			
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:			
1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371 2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US) 6. <input type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has <b>NOT</b> expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).			
<b>ITEMS 11. TO 16. below concern other document(s) or information included:</b>			
11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input checked="" type="checkbox"/> A <b>FIRST</b> preliminary amendment. <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment. 14. <input type="checkbox"/> A substitute specification. 15. <input type="checkbox"/> A change of power of attorney and/or address letter. 16. <input checked="" type="checkbox"/> Other items or information: Courtesy copy of International Application w/International Search Report; and PCT/IPEA/409 (4 pp.) w/1 amended sheet.			

U.S. APPLICATION NO. (if known) <b>09/720102</b> (37 CFR 1.50)		INTERNATIONAL APPLICATION NO. PCT/FI99/00568		ATTORNEY DOCKET NO. 2530-109	
17. <input checked="" type="checkbox"/> The following fees are submitted: <b>Basic National Fee (37 CFR 1.492)(a)(1)-(5):</b>				<u>CALCULATIONS</u>	<u>PTO USE ONLY</u>
Search Report has been prepared by the EPO or JPO				\$ 860.00	
International preliminary examination fee paid to USPTO (37 CFR 1.482)				\$ 690.00	
No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2))				\$ 710.00	
Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO				\$1,000.00	
International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4)				\$ 100.00	
<b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>				<b>\$1,000.00</b>	
Surcharge of \$130.00 for furnishing the oath or declaration later than [ ] 20 [X] 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
Claims	Number Filed	Number Extra	Rate		
Total Claims	18 -20 =	0	X \$18.00	\$	
Independent Claims	1 - 3 =	0	X \$80.00	\$	
Multiple dependent claim(s) (if applicable)			+ \$270.00	\$	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				<b>\$1,000.00</b>	
Reduction by 1/2 for filing by small entity, if applicable. Applicant hereby claims Small Entity status. (Note 37 CFR 1.9, 1.27, 1.28).				\$	
<b>SUBTOTAL =</b>				<b>\$1,000.00</b>	
Processing fee of \$130.00 for furnishing the English translation later [ ] 20 [ ] 30 than months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
<b>TOTAL NATIONAL FEE =</b>				<b>\$1,000.00</b>	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$	
<b>TOTAL FEES ENCLOSED =</b>				<b>\$1,000.00</b>	
				Amount to be refunded	\$
				charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$1,000.00 to cover the above fees is enclosed.					
b. <input type="checkbox"/> Please charge my Deposit Account No. 02-2135 in the amount of \$0.00 to cover the above fees. A duplicate copy of this sheet is enclosed.					
c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 02-2135. A duplicate copy of this sheet is enclosed.					
<b>NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.</b>					
SEND ALL CORRESPONDENCE TO: George R. Repper Rothwell, Figg, Ernst & Manbeck 555 13th St., N.W. Washington, D.C. 20004 Phone: 202/783-6040					
 Signature George R. Repper Name 31.414 Registration Number					

09/720102

JC01 Rec'd PCT/PTO 2 1 DEC 2000

2530-109  
GRR:mys

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of )  
 )  
Arthur van BREMPT et al. )  
 )  
Application No. §371 of )  
PCT/FI99/00568 )  
 )  
Filed: Concurrently Herewith )  
 )  
For: A PROCESS FOR PREPARATION OF )  
COMPOUND FERTILIZER GRANULES )

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents  
Washington, D.C. 20231

Dear Sir:

Prior to calculation of the filing fee and examination on the merits, please enter the following amendments.

IN THE ABSTRACT:

Please add the accompanying Abstract of the Disclosure which is provided on a separate sheet.

IN THE CLAIMS:

- Claim 1, line 8, delete "molten or".
- Claim 3, line 1, delete "or 2" and "molten or".
- Claim 4, line 1, change "any of claims 1-3" to --claim 1--.
- Claim 6, line 1, change "any of claims 1-5" to --claim 1--.
- Claim 7, line 1, change "any of claims 1-6" to --claim 1--.
- Claim 8, line 1, change "any of claims 1-6" to --claim 1--.
- Claim 9, line 1, change "any of claims 1-8" to --claim 1--.
- Claim 10, line 1, change "any of claims 1-9" to --claim 1--.
- Claim 11, line 1, delete "or 10".
- Claim 12, line 1, change "any of claims 1-11" to --claim 1--.
- Claim 13, line 1, change "any of claims 1-12" to --claim 1--.
- Claim 15, line 1, change "any of claims 1-14" to --claim 1--.
- Claim 16, line 1, change "any of claims 1-15" to --claim 1--.
- Claim 18, line 1, change "any of claim 1-17" to --claim 1--.

REMARKS

The above amendments are being made to further define the invention and to eliminate multiple dependencies in the claims. These amendments do not add to or depart from the original disclosure, or constitute prohibited new matter.

Respectfully submitted,



By

George R. Repper, Registration No. 31,414  
Attorney for Applicants  
ROTHWELL, FIGG, ERNST & MANBECK p.c.  
Suite 701-E, 555 13th Street, N.W.  
Washington, D.C. 20004  
Telephone: (202)783-6040

A process for the preparation of compound fertilizer granules

The present invention relates to a process for the preparation of compound fertilizer granules by using solid granulation.

- 5 The term "compound fertilizer" is defined and used with several different meanings; it contains at least two of the plant nutrients nitrogen, phosphorus, and potassium. Compound fertilizers are produced chemically or by blending. They shall be in the form of granules, pellets, prills, or crystals and shall be free-flowing.

- 10 Compound fertilizers are manufactured and frequently used because they are convenient to produce, transport, store and apply and because they fulfil local or regional nutrient requirements, especially basal nutrient needs well. In addition to containing various ratios of the primary nutrients ( $N + P_2O_5 + K_2$ ), the compound fertilizers may contain certain secondary and micronutrients specific to the crop needs in particular agroclimatic regions.

- 15 Granulated fertilizers have several advantages over powders, particularly in decreasing the quantity of dust, improving uniformity of flow when fertilizers are applied and segregation when they are blended.

- 20 In classifying the granulation methods, the physical properties of the materials to be granulated will be used. According to the density of the materials the following three groups may be distinguished: granulation of solids, granulation of slurries or of melts and granulation of fluids simultaneously with the reaction by which the product is formed.

- 25 Basic processes for manufacturing compound fertilizers are: Steam/water granulation, Chemical granulation or complex or slurry granulation, Drop forming or prilling, Compaction granulation and Dry mixing or blending.

- 30 The principal mechanisms responsible for initial fertilizer granule formation and subsequent growth are agglomeration and accretion. The known and widely applied compound fertilizer granulation methods are well reported for example in "Fertilizer Manual", Kluwer Academic Publishers, 1998, p. 434-451 and "Studies of Granulation of Compound Fertilizers Containing Urea: A Literature Review", G.C. Hicks, National Fertilizer Development Center; Bull Y-108, 15 pp., 1976.

Accretion is a process in which layer upon layer of a fluid material is applied to a solid particle causing it to grow in size; for example slurry-type granulation processes used to produce DAP, MAP, TSP, and some nitrophosphate compounds are accretion-type of granulation processes.

- 5 Agglomeration or granulation of solid particles is a classical method to granulate fertilizers, for example NPK products. In most agglomeration-type NPK formulations, 50-75% of the raw materials are fed as solid particles. The (premixed) raw materials are fed to a granulator where agglomeration is initiated. In the granulator steam and/or water or other liquid is added to provide sufficient liquid to enhance granulation. In same processes a small amount ammonia may also be added to promote granulation and improve product quality by increasing the CHR (critical relative humidity) and decreasing the acidity. The solid particles are assembled and joint into granules by a combination of mechanical interlocking and cementing.

- 15 A number of industrial scale processes to manufacture compound fertilizers are developed and applied. In the steam/water granulation process steam and/or water or scrubber liquid is added into the granulator to provide sufficient liquid phase and plasticity to cause the dry raw materials to agglomerate into the product-size granules required.

- 20 The use of urea as a N-source for fertilizers of the different types and grades has established. Solid urea with quite high biuret content (0,8-2,0 wt-%) is mainly used for direct application to the soil and weak aqueous urea solutions with low biuret (max 0,3 wt-%) are used as foliage sprays.

The use of urea has also established in the manufacture of (granular) compound fertilizers based on for example superphosphate or ammonium phosphate.

- 25 The conventional wet granulation is not a suitable method for producing formulations containing urea, particularly when potassium chloride is also present, because the product is very hygroscopic and therefore difficult and expensive to dry.

- 30 In the chemical granulation beside a great amount of solid raw materials, water, steam, scrubber liquid, and/or ammonia and acid are fed to the granulator; the granules are formed mostly by agglomeration but in some processes granule formation may occur by accretion, too.

Drop formation or prilling, compaction granulation, dry mixing or blending, etc. are also applied quite widely to produce different granular fertilizer formulations.

5 Because some water or moisture is always present in most traditional granulation processes, drying is an obligatory, difficult and expensive stage of the processes and cause the need of a separate dryer construction. To solve problems of granulation, product quality and drying different fertilizer grade-dependent processes are development.

10 A granulation process is described by Doshi, S.R. in the article "Fusion blend", Fertilizer Research vol. 30(1): p.87-97, 1991. Water (or steam) has been used to agglomerate solids either in powder, prilled or granulated form but no other liquids such as ammonia, phosphoric acid, or nitric acid are involved in the described process; still drying is essential.

15 Some water or moisture is always included in the process. The process is temperature and material moisture-related. For example, for the most agglomeration-type NPK fertilizers a liquid phase of about 300 kg/t of product is shown to be optimal.

20 Patent publication GB 1,189,398 (Sumitomo) discloses a process for producing a NK fertilizer which process comprises spraying a liquid mixture of urea, potassium chloride, gypsum and 1-10% by weight of water onto the solid material in a granulator. No drying is used. However, the amount of water added into the process is high enough to keep urea in dissolved state and the final product has a quite great water content of 1-2% by weight.

25 Patent publication US 4,138,750 (TVA) discloses a process for the production of fertilizers from phosphoric acid, sulfuric acid, anhydrous ammonia and urea where a specially designed pipe-cross reactor is used to produce a homogenous melt or slurry of low moisture content from phosphoric acid, sulfuric acid and anhydrous ammonia. The pipe-cross reactor eliminates the need for a preneutralizer and in addition, because of the low melt or slurry moisture content, the dryer is eliminated. The neutralization reaction heat is drying the material in the pipe-cross reactor.

30 Because of the water/moisture content of the raw materials and products, process and product quality problems, like increased hygroscopicity and plasticity, will often occur when fertilizers are granulated by using steam/water and chemical granulation processes; particularly when, for example SSP, TSP and/or urea is present in the product. The hygroscopicity and plasticity complicate drying.

screening and crushing operations, and furthermore, the storage properties of those compound fertilizers are often inferior to those of fertilizers that do not contain these substances.

5 The present invention is developed to solve the granulation, product quality, and storage etc. problems in manufacturing of compound fertilizers. The present invention relates to a process for the preparation of compound fertilizers such as NPK, NK etc., where solid raw materials are mixed in a mixer and fed to a granulator, where to hot air is also fed. The raw materials are granulated without the aid of water or any other liquid such as ammonia, phosphoric acid or sulfuric acid.  
10 Thus, the granulation is a true solid granulation process. Because water or any other liquid is not added, there is no need for drying the granulated product. Further more the physical quality of the product is good, too.

Particularly, the process of the present invention has great advantages to the known granulation methods which require higher temperatures at the drying phase.  
15 Particularly, controlling of the humidity and drying temperature is important and difficult; the high temperature may cause melting of the granulated material and it will stick to the interior walls and flights of the dryer near the discharge end. The optimal values for humidity and temperature vary greatly from product to product.

Thus, the present invention provides a process for the preparation of compound  
20 fertilizer granules containing at least two of the plant nutrients nitrogen, phosphorus and potassium, said process comprising the steps of:  
providing a solid feed material comprising at least one solid fertilizer raw material and optionally recycle material,  
feeding the feed material or a part thereof into a melter for melting a desired portion  
25 thereof and keeping said portion in molten state,  
feeding the molten or partly molten material and optionally other desired solid raw materials to a granulator to obtain a granulated product, and  
cooling and optionally screening the granulated product to obtain dry compound fertilizer granules having a desired size distribution,  
30 provided that no water or aqueous liquid is introduced into the process.

The melting of the feed material or a part thereof in the melter can be effected by introducing hot air into the melter. The melting can also be effected by other means, for example by heaters.



According to a preferred embodiment of the invention the process is carried out continuously, and the molten portion of the feed material is kept constant during the process by controlling the flow rate of the feed material and the temperature of the hot air introduced into the melter. The optimal proportion of the molten feed material is dependent on the grade of the fertilizer wanted and the raw materials used. The optimal proportion of the molten material can for example be about 10-40 wt-%, preferably about 10-25 wt-%, more preferably about 12-20 wt-%, depending on the grade.

When melting is carried out by the aid of hot air a suitable temperature of the hot air introduced into the melter is between 200 and 550 °C. At the melter outlet the hot air has a temperature of about 90 °C to 120 °C.

Suitably the temperature of the molten or partly molten feed material leaving the melter is between 70 °C and 135 °C, preferably between 70 °C and 110 °C.

The process of the invention can be carried out either by introducing all individual components of the raw materials into the melter or by introducing one or some of the individual components of the raw materials into the melter and the rest of the components into the granulator.

The material to be fed into the melter and/or granulator can be preheated. This is preferred in view of the temperature control of the process. The material can suitably be preheated to a temperature in the range from about 80 °C to about 110 °C.

The granulation temperature can vary depending on the formula of the fertilizer. The granulation temperature is preferably between about 75 °C and about 125 °C, more preferably between about 80 °C and about 125 °C.

The temperature of the cooled granulated product to be screened is typically between about 40 °C and 60 °C.

Typical solid fertilizer raw materials which can be used in the present invention are e.g. urea, diammonium phosphate (DAP),  $K_2SO_4$  (SOP), monoammonium phosphate (MAP), phosphate rock, potassium chloride (MOP i.e. KCl), single superphosphate (SSP), triple superphosphate (TSP), ammonium sulfate (AS) and ammonium chloride (AC).

Preferably the fertilizer raw materials comprise urea, especially urea prills, and at least one other fertilizer raw material.

Additionally magnesium sulfate and/or one or several trace elements i.e. micro-nutrients, such as boron, can be added.

Furthermore bentonite, calcite, calcium oxide, calcium sulfate (anhydrous or hemihydrate), dolomite and/or sand and/or any other conventionally used filler can be added.

According to the present invention all solid raw materials (solid fertilizer raw materials and optionally recycle material, micro nutrients and fillers) can be introduced into the melter. However, it is also possible to introduce a part of the solid raw materials into the melter and the remaining solid raw materials into the granulator.

In a preferred embodiment the process of the invention comprise the step of screening the granulated product to obtain dry compound fertilizer granules having a size of 2 to 5 mm.

The undersize material ( $< 2$  mm) and the oversize material ( $> 5$  mm) obtained in the screening can be recirculated as said recycle material. Optionally the oversize material can be milled after the screening before being recirculated. The temperature of the recycle material from the screening is typically about  $60^{\circ}\text{C}$  or less.

The melter and granulator can be separate units but the melter and granulator can also be part of the same equipment.

This invention has advantages over the traditional granulation methods of the prior art technology because the raw materials are granulated without the aid of any water or any other liquid such as ammonia, phosphoric acid or sulfuric acid. Because water or any other liquid is not added, there is no need for drying of the product. This makes the granulation operation more simple and investment costs less expensive because no separate equipment for drying is needed.

The final product will have a low water content (0.2-0.6 wt-%) originating from the raw materials. No supplementary drying is required. The water content of the products produced by traditional methods is normally about 1-2 wt-% causing already mentioned caking and applying problems.

The invention is illustrated in and by the following examples. Additionally the strenght of the product granules obtained in the following examples was checked after a 3 months' storage, and the strenght was found to be unchanged.

**Example 1**

Bench scale process for solid granulation.

Formulas (kg/t)

	<b>GRADE</b>		
	15-15-15 DAP+SSP	15-15-15 MAP+Sand	17-17-17 MAP+NH <sub>4</sub> Cl
Raw material			
Urea	249	255	204
MAP(Lithuania 11-50)	-	300	340
DAP(Pernis 17-45)	210	-	-
SSP(Lithuania 19%)	287	-	-
NH <sub>4</sub> Cl (N 26%)	-		153
KCl (K <sub>2</sub> O 60%)	250	250	284
Sand	-	175	-

- 5 The mixture of the solid raw materials was fed to the bench scale granulator. Urea was added as prills. The melting of the mixture happened with hot air at the beginning of the granulator. Granulation was carried out at the granulator and partly at the cooler.

The process conditions and results are shown in Table 1.

**Table 1**

	<b>GRADE</b>		
	15-15-15 DAP+SSP	15-15-15 MAP+Sand	17-17-17 MAP+NH <sub>4</sub> Cl
Process conditions:			
Feed + recycle kg/h	8.3	10.1	11.9
Recycle ratio	0.2	0.2	0.2
Air heater			
- temperature °C	336	316	322
- pressure bar	1.8	1.8	1.8
Temperature of product			
granulator outlet °C	97	92	97
cooler outlet	30	32	35
Granulation	Good	Very good	Good

## Product properties:

H <sub>2</sub> O (KF) %	0.25	0.15	0.28
N %	15.2	16.1	18.2
P <sub>2</sub> O <sub>5</sub> total %	15.9	15.0	17.1
K <sub>2</sub> O %	15.8	16.7	18.5
Granule strength N	52	40	50
Abrasion %	0	0.2	0.7
Shattering %	37	32	45
CRH %	34	35	43
Moisture absorption 80% RH			
2 h %	2.8	2.7	3.2
4 h %	5.7	5.5	6.2
6 h %	8.8	8.3	9.1

The grade 15-15-15 granulated better when it contained MAP + sand than DAP + SSP.

- 5 The grade 17-17-17 containing ammonium chloride granulated good, too. Ammonium chloride reacted partly with urea and formed urea · NH<sub>4</sub>Cl. Nutrient content of each product was good. Physical properties of the products were good; the products were very dry.

**Example 2**

Bench scale process for solid granulation

<b>GRADE</b>		<b>NK 16-0-31</b>	
		<b>2A</b>	<b>2B</b>
5	Formula	16-0-31	16-0-31
		Filler	Filler $\text{CaSO}_4$
		bentonite	hemihydrate
		kg/t	kg/t
		Urea (prills)	348
10	KCl (white)	517	517
	Bentonite	125	-
	$\text{CaSO}_4 \cdot 0.5\text{H}_2\text{O}$	-	125
	(as dry matter)		

- 15 The mixture of solid raw materials was fed with the recycle to the bench scale granulator. Melting happened with hot air at the beginning of the granulator. Granulation has been carried out at the granulator and partly at the cooler.

The products were coated with Esso coating oil 2 kg/t + talc 3 kg/t.

- 20 Very good or good granulation was obtained with a good product quality. However, the great humidity of air during the process caused some immediate increase of the water content of the final product.

The process conditions and results of the product tests are shown in Table 2.

**Table 2**  
**GRADE**

			<b>NK 16-0-31</b>	
			2A	2B
			16-0-31	16-0-31
			Filler bentonite	Filler CaSO <sub>4</sub> hemihydrate
5	Feed + recycle kg/h		9.0	9.0
	Recycle ratio		0.7	0.4
	Air heater			
10	- temperature	°C	294	238
	- pressure	bar	1.6	1.6
	Temperature of fert	°C		
	- granulator outlet		104	88
	- cooler outlet		28	27
15	Granulation		Very good	Good
	Product properties			
	Chemical analyses			
	Water ( KF )	%	0.77	0.78
	Urea - N	%	16.6	16.8
20	N	%	16.6	16.8
	K <sub>2</sub> O	%	31.8	30.9
	S	%	0.51	3.0
	pH		7.3	5.6
	Physical properties			
25	Granule strenght	N	27	41
	Abrasion	%	1.3	1.1
	Volume weight	kg/l	0.77	0.80
	Flowability	kg/min	4.83	4.80
	Shattering	%	52	45
30	CRH	%	40	38
	Moisture absorption			
	80% RH			
	2 h	%	2.9	2.7
	4 h	%	5.0	4.5
35	6 h	%	7.0	6.8

**Example 3**

Bench scale process for solid granulation

	<b>GRADE</b>	<b>18-12-6+1.5MgO</b>
5		kg/t
	Urea (prills)	172
	KCl (white)	100
	Kovdor phosphate	155
	DAP (Pernis) 17-45	143
10	AS (Leuna)	366
	MgSO <sub>4</sub>	53

The mixture of solid raw materials was fed with the recycle to the bench scale granulator. Melting happened with hot air at the beginning of the granulator. Granulation has been carried out at the granulator and partly at the cooler.

- 15 The products were coated with Esso coating oil 2 kg/t + talc 3 kg/t.

Very good granulation was obtained with a good product quality. The process conditions and results of product tests are shown in Table 3.

Table 3

GRADE		18-12-6+1.5MgO
	Feed + recycle kg/h	9.0
	Recycle ratio	0.6
5	Air heater	
	- temperature °C	233
	- pressure bar	1.6
	Temperature of fert °C	
	- granulator outlet	98
10	- cooler outlet	28
	Granulation	Good
Product properties		
Chemical analyses		
	Water ( KF ) %	0.36
15	Urea - N %	8.5
	NH <sub>4</sub> - N %	9.7
	N %	18.2
	P <sub>2</sub> O <sub>5</sub> - Total %	11.3
	P <sub>2</sub> O <sub>5</sub> - NAC %	6.0 (53%)
20	P <sub>2</sub> O <sub>5</sub> - WS %	5.5 (49%)
	K <sub>2</sub> O %	8.4
	Mg %	1.3
	S %	10.8
	pH	5.8
25	Physical properties	
	Granule strenght N	41
	Abrasion %	0.6
	Volume weight kg/l	0.84
	Flowability kg/min	4.88
30	Shattering %	59
	CRH %	40
Moisture absorption		
80% RH		
	2 h %	3.3
35	4 h %	5.2
	6 h	



**Example 4**

Bench scale process for solid granulation

5	<b>GRADE</b>	<b>12-12-17+2 MgO + 0.5 B<sub>2</sub>O<sub>3</sub></b>
		kg/t
	Urea (crushed)	264
	Morocco phosphate	270
	TSP (P <sub>2</sub> O <sub>5</sub> 45%)	89
10	KCl (white)	284
	MgSO <sub>4</sub>	64
	Colemanite	6

15 The mixture of solid raw materials and recycle was preheated to about 100 °C in the feeding screw of the granulator. Melting happened with hot air at the granulation drum. Granulation has been carried out at the granulator and partly at the cooling drum.

The products were coated with SK Fert FW5 AG 2 kg/t + talc 3 kg/t.

Very good or good granulation was obtained with a good product quality. The process conditions and results of product tests are shown in Table 4.

Table 4

GRADE		12-12-17+2 MgO + 0.5MgO	
	Feed + recycle kg/h		5.3
	Recycle ratio		0.6
5	Granulation temperature °C	About 120	
	Air from cooler	"	27
	Granulation	Good	
Product properties			
Chemical analyses			
10	Water (Kf)	%	0.35
	Urea - N	%	12.4
	P <sub>2</sub> O <sub>5</sub> - Total	%	12.2
	P <sub>2</sub> O <sub>5</sub> - NAC	%	6.0 (49%)
	P <sub>2</sub> O <sub>5</sub> - WS	%	2.8 (23%)
15	K <sub>2</sub> O	%	18.8
	Mg	%	1.5
	B	%	750
	pH		4.8
Physical properties			
20	Granule strenght	N	40
	Abrasion	%	0.1
	Volume weight	kg/l	0.82
	Flowability	kg/min	5.4
	CRH	%	23
25	Moisture absorption		
	80% RH		
	2 h	%	3.2
	4 h	%	5.5
	6 h		8.0

30

**Example 5**

Bench scale process for solid granulation

5	<b>GRADE</b>	<b>12-6-24</b>
		kg/t
	Urea (crushed)	264
	SSP (P <sub>2</sub> O <sub>5</sub> 20%)	100
	Morocco phosphate	130
10	KCl (white)	400
	Colemanite	6
	Bentonite	80

15 The mixture of solid raw materials and recycle was preheated to about 100 °C in the feeding screw of the granulator. Melting happened with hot air at the granulation drum. Granulation has been carried out at the granulator and partly at the cooling drum.

The products were coated with SK Fert FW5 AG 2 kg/t + talc 3 kg/t.

20 Very good or good granulation was obtained with a good product quality. The process conditions and results of product tests are shown in Table 5.

Table 5

GRADE		12-6-24
	Feed + recycle kg/h	5.1
	Recycle ratio	0.84
5	Granulation temperature °C	About 120
	Air from cooler "	28
	Granulation	Very good
Product properties		
Chemical analyses		
10	Water (KF) %	0.27
	Urea - N %	13.1
	P <sub>2</sub> O <sub>5</sub> - Total %	6.0
	P <sub>2</sub> O <sub>5</sub> - NAC %	2.9 (48%)
	P <sub>2</sub> O <sub>5</sub> - WS %	0.84 (14%)
15	K <sub>2</sub> O %	25.8
	B %	850
	pH	6.1
Physical properties		
	Granule strenght N	39
20	Abrasion %	0.1
	Volume weight kg/l	0.84
	Flowability kg/min	5.6
	CRH %	15
Moisture absorption		
25	80% RH	
	2 h %	2.1
	4 h %	4.1
	6 h	6.0

**Example 6****GRADE****15-15-15**

5		
	Urea (crushed)	285 kg/t
	Urea melted	100 %
	DAP	117 kg/t
	Yunnan rock phosphate	330 kg/t
10	MOP	255 kg/t
	Bentonite	6 kg/t

Urea was melted in a separate reactor and mixed with the other raw materials preheated to 90 °C. The temperature at the beginning of the granulation was 110.4 °C and at the end of the granulation 103.2 °C. The duration of the granulation stage was 4 minutes.

	Product properties:	
	H <sub>2</sub> O (KF)	0.09
20	Granule strenght N	34.5

Very good granulation was obtained.

**Example 7**

25

Bench scale process for solid granulation

**GRADE****15-15-15**

30		
	Urea (46 %)	276 kg/t
	DAP (17-45)	142 kg/t
	Rock phosphate	270 kg/t
	(P <sub>2</sub> O <sub>5</sub> 32 %)	
35	K <sub>2</sub> SO <sub>4</sub>	300 kg/t
	(K <sub>2</sub> O 50 %)	

The mixture of solid raw materials and recycle was preheated to about 100 °C with IR in the feeding screw of the drum. The outer wall of the granulation drum was

heated with IR too. Urea was crushed beforehand. Small amount of hot air was used in the melting of urea in the granulation drum. Drying drum worked as cooler.

The products were coated with SK Fert FW5 AG 2 kg/t + talc 3 kg/t.

5

Process conditions:

Feed and recycle kg/h 5.07

Recycle ratio 0.75

Recycle heater °C 179

10

Granulation drum

x Outside °C 268

x Inside " 117

Air to the drum " 287

15 Air to cooler " 24

Air from cooler " 28

Granulation Good

Product properties:

20 H<sub>2</sub>O (KF) % 0.09

N " 15.5

P<sub>2</sub>O<sub>5</sub> total " 15.4

K<sub>2</sub>O " 16.1

S " 6.6

25

Granule strenght N 30

Abrasion % 0.4

Shattering % 28

CRH % 18

30 Moisture abs.

80 % RH

2 h % 2.6

4 h % 4.8

6 h % 6.6

35

SOP based 15-15-15 granulated good.

## Claims

1. A process for the preparation of compound fertilizer granules containing at least two of the plant nutrients nitrogen, phosphorus and potassium, said process comprising the steps of:
- 5 providing a solid feed material comprising at least one solid fertilizer raw material and optionally recycle material,  
feeding the feed material or a part thereof into a melter for melting a desired portion thereof and keeping said portion in molten state,  
feeding the ~~molten or~~ partly molten material and optionally other desired solid raw
- 10 materials to a granulator to obtain a granulated product, and  
cooling and optionally screening the granulated product to obtain dry compound fertilizer granules having a desired size distribution,  
provided that no water or aqueous liquid is introduced into the process.
2. A process according to claim 1, wherein the process is carried out
- 15 continuously, and the molten portion of the feed material is kept constant during the process by controlling the flow rate of the feed material and the temperature of the melter.
3. A process according to claim 1 or 2, wherein the temperature of the ~~molten or~~ partly molten feed material is between 70 °C and 135 °C.
- 20 4. A process according to any of claims 1-3, wherein the melting is effected by introducing hot air into said melter.
5. A process according to claim 4, wherein the temperature of the hot air introduced into the melter is between 200 °C and 550 °C.
6. A process according to any of claims 1-5, wherein from 10 to 40% by weight
- 25 of the feed material melts in the melter.
7. A process according to any of claims 1-6, wherein said solid feed material to be fed into the melter comprises all individual components of the raw materials.
8. A process according to any of claims 1-6, wherein said solid feed material to
- 30 be fed into the melter comprises one or some of the individual components of the raw materials, and the rest of the components is fed to the granulator.

9. A process according to any of claims 1-8, wherein said solid feed material to be fed into the melter is preheated.
10. A process according to any of claims 1-9, wherein the solid raw material to be  
5 fed to the granulator is preheated.
11. A process according to claim 9 or 10, wherein the material is preheated to a temperature in the range from 80 °C to 110 °C.
- 10 12. A process according to any of claims 1-11, wherein the granulation temperature is in the range from 75 °C to 125 °C, preferably from 80 °C to 125 °C.
13. A process according to any of claims 1-12, wherein the fertilizer raw materials are selected from the group consisting of urea, diammonium phosphate (DAP),  
15  $K_2SO_4$  (SOP), monoammonium phosphate (MAP), potassium chloride (MOP), phosphate rock, single superphosphate (SSP), triple superphosphate (TSP), ammonium sulfate (AS) and ammonium chloride (AC).
14. A process according to claim 13, wherein the fertilizer raw materials comprise urea and at least one other of said fertilizer raw materials.
- 20 15. A process according to any of claims 1-14, wherein additionally at least one material selected from the group consisting of magnesium sulfate and micronutrients is introduced into the process.
16. A process according to any of claims 1-15, wherein additionally at least one filler selected from the group consisting of bentonite, calcite, calcium oxide,  
25 anhydrous calcium sulfate, calcium sulfate hemihydrate, dolomite, and sand, is introduced into the process.
17. A process according to claim 1, wherein the undersize material and the oversize material obtained in the screening are recirculated as said recycle material, said oversize material optionally being milled after the screening.
- 30 18. A process according to any of claims 1-17, wherein the moisture content of the dry compound fertilizer granules is below 0.6% by weight, preferably below 0.3% by weight.



## ABSTRACT OF THE DISCLOSURE

The invention relates to a process for the preparation of compound fertilizer granules containing at least two of the plant nutrients nitrogen, phosphorus and potassium, said process including the steps of: providing a solid feed material including at least one solid fertilizer raw material and optionally recycle material, feeding the feed material or a part thereof into a melter for melting a desired portion thereof and keeping said portion in molten state, feeding the molten or partly molten material and optionally other desired solid raw materials to a granulator to obtain a granulated product, and cooling and optionally screening the granulated product to obtain dry compound fertilizer granules having a desired size distribution, provided that no water or aqueous liquid is introduced into the process.

**Declaration and Power of Attorney  
For Patent Application  
(Sole/Joint)**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I verily believe I am the original, first and sole inventor (if only one name is listed below) or a joint inventor (if plural inventors are named below) of the subject matter which is claimed and for which a patent is sought, on the invention entitled \_\_\_\_\_

A process for the preparation of compound fertilizer granules

\_\_\_\_\_ the specification of which (Check One)

\_\_\_\_\_ is attached hereto.

OR

☒ was filed on \_\_\_\_\_ as

☐ Application Serial No. \_\_\_\_\_

☒ International Application No. PCT/ FI99/00568

and was amended on \_\_\_\_\_

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application..

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or any PCT application having a filing date before that of the application on which priority is claimed:

**PRIOR FOREIGN APPLICATION(S)**

			Priority Claimed
981490	Finland	29 June 1998	Yes: <input checked="" type="checkbox"/> No: _____
(Number)	(Country)	(Day/Month/Year Filed)	
982013	Finland	18 September 1998	Yes: <input checked="" type="checkbox"/> No: _____
(Number)	(Country)	(Day/Month/Year Filed)	
_____	_____	_____	Yes: _____ No: _____
(Number)	(Country)	(Day/Month/Year Filed)	



I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below:

APPLICATION NUMBER: \_\_\_\_\_ FILING DATE: \_\_\_\_\_  
APPLICATION NUMBER: \_\_\_\_\_ FILING DATE: \_\_\_\_\_

I or we hereby appoint the registered practitioner(s) associated with Customer Number 6449 to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith. Direct all correspondence about the application to Customer Number 6449.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful

false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of Sole or First Inventor		Inventor's Signature	Date
Arthur van Brempt			18 January 2001
Residence	Daalstraat 111, B-1852 Grimbergen, Belgium		Citizenship Belgian
Mailing Address same as above			
Full Name of Second Joint Inventor, if any		Inventor's Signature	Date
Juhani Poukari			18 January 2001
Residence	Tinankuja 4 D 24, FIN-12430 Masala, Finland		Citizenship Finnish
Mailing Address same as above FIN			
Full Name of Third Joint Inventor, if any		Inventor's Signature	Date
Residence		Citizenship	
Post Office Address			
Full Name of Fourth Joint Inventor, if any		Inventor's Signature	Date
Residence		Citizenship	
Post Office Address			
Full Name of Fifth Joint Inventor, if any		Inventor's Signature	Date
Residence		Citizenship	
Post Office Address			
Full Name of Sixth Joint Inventor, if any		Inventor's Signature	Date
Residence		Citizenship	
Mailing Address			
Full Name of Seventh Joint Inventor, if any		Inventor's Signature	Date
Residence		Citizenship	
Post Office Address			
Full Name of Eighth Joint Inventor, if any		Inventor's Signature	Date
Residence		Citizenship	
Mailing Address			

Patent Application Declaration

Page 2 of 2